Titan 'EDGE'

contemporary elegance

Flat rooflight data sheet

Polished EDGE-to-EDGE Glass

- Ultra-contemporary unrivalled aesthetics
- Water glides off the surface
- No vulnerable or messy sealants on the glass surface

Pilkington Active Solar Control Glass as standard

- 6mm toughened external pane efficiently reflects heat
- Low maintenance easy clean coating

Laminated inner pane as standard

- · Safety laminated glass will never shatter
- Security laminated glass is incredibly difficult to break
- Sun bleaching laminated glass eliminates 98% of unwanted UV
- Sound reduction laminated glass significantly reduces noise pollution

Thermal Performance

- Thermally broken aluminium frame
- 20mm Warm Edge spacer bar
- Argon gas filled sealed unit
- U Value of 1.3w/m2k

Simple Installation

- Fixed from inside no security issues or potential leak points
- Fixing straps fitted in the factory
- It's a 'one piece unit'. No extra bits to fix on after

Finishing
• Plasterboard pocket fitted as standard to make finishing easy

Technical

- Glass make-up
- Outer pane polished edge 6mm toughened easy clean solar control with blackened border
- 20mm Warm Edge spacer bar, sealed with UV stable sealant. Argon gas filled
- Inner Pane-6.4mm laminated Soft Coat safety Glass
- Recommended pitch 5 degrees





